



O 環 P 規格

P-Type O-Ring Size List



單位 unit : mm

| 材質 | 橡膠 | 橡膠 (高壓) | 氟橡膠 (耐熱) | 矽橡膠 |
|----|-------|---------|----------|-----|
| | NBR70 | NBR90 | VT | SE |

| O 環 P 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|----------|---------|---------|------|
| P-2 | 1.8 | 5.6 | 1.9 |
| P-3 | 2.8 | 6.6 | 1.9 |
| P-4 | 3.8 | 7.6 | 1.9 |
| P-5 | 4.8 | 8.6 | 1.9 |
| P-6 | 5.8 | 9.6 | 1.9 |
| P-7 | 6.8 | 10.6 | 1.9 |
| P-8 | 7.8 | 11.6 | 1.9 |
| P-9 | 8.8 | 12.6 | 1.9 |
| P-10 | 9.8 | 13.6 | 1.9 |
| P-10A | 9.8 | 14.6 | 2.4 |
| P-11 | 10.8 | 15.6 | 2.4 |
| P-11.2 | 11 | 15.8 | 2.4 |
| P-12 | 11.8 | 16.6 | 2.4 |
| P-12.5 | 12.3 | 17.1 | 2.4 |
| P-13 | 12.8 | 17.6 | 2.4 |
| P-14 | 13.8 | 18.6 | 2.4 |
| P-15 | 14.8 | 19.6 | 2.4 |
| P-16 | 15.8 | 20.6 | 2.4 |
| P-17 | 16.8 | 21.6 | 2.4 |
| P-18 | 17.8 | 22.6 | 2.4 |
| P-19 | 18.8 | 23.6 | 2.4 |
| P-20 | 19.8 | 24.6 | 2.4 |
| P-21 | 20.8 | 25.6 | 2.4 |
| P-22 | 21.8 | 26.6 | 2.4 |
| P-22A | 21.7 | 28.7 | 3.5 |
| P-22.4 | 22.1 | 29.1 | 3.5 |
| P-24 | 23.7 | 30.7 | 3.5 |
| P-25 | 24.7 | 31.7 | 3.5 |
| P-25.5 | 25.2 | 32.2 | 3.5 |
| P-26 | 25.7 | 32.7 | 3.5 |
| P-28 | 27.7 | 34.7 | 3.5 |
| P-29 | 28.7 | 35.7 | 3.5 |
| P-29.5 | 29.2 | 36.2 | 3.5 |
| P-30 | 29.7 | 36.7 | 3.5 |
| P-31 | 30.7 | 37.7 | 3.5 |
| P-31.5 | 31.2 | 38.2 | 3.5 |
| P-32 | 31.7 | 38.7 | 3.5 |
| P-34 | 33.7 | 40.7 | 3.5 |

| O 環 P 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|----------|---------|---------|------|
| P-35 | 34.7 | 41.7 | 3.5 |
| P-35.5 | 35.2 | 42.2 | 3.5 |
| P-36 | 35.7 | 42.7 | 3.5 |
| P-38 | 37.7 | 44.7 | 3.5 |
| P-39 | 38.7 | 45.7 | 3.5 |
| P-40 | 39.7 | 46.7 | 3.5 |
| P-41 | 40.7 | 47.7 | 3.5 |
| P-42 | 41.7 | 48.7 | 3.5 |
| P-44 | 43.7 | 50.7 | 3.5 |
| P-45 | 44.7 | 51.7 | 3.5 |
| P-46 | 45.7 | 52.7 | 3.5 |
| P-47A | 46.6 | 58 | 5.7 |
| P-48 | 47.7 | 54.7 | 3.5 |
| P-48A | 47.6 | 59 | 5.7 |
| P-49 | 48.7 | 55.7 | 3.5 |
| P-50 | 49.7 | 56.7 | 3.5 |
| P-50A | 49.6 | 61 | 5.7 |
| P-52 | 51.6 | 63 | 5.7 |
| P-53 | 52.6 | 64 | 5.7 |
| P-55 | 54.6 | 66 | 5.7 |
| P-56 | 55.6 | 67 | 5.7 |
| P-58 | 57.6 | 69 | 5.7 |
| P-60 | 59.6 | 71 | 5.7 |
| P-62 | 61.6 | 73 | 5.7 |
| P-63 | 62.6 | 74 | 5.7 |
| P-65 | 64.6 | 76 | 5.7 |
| P-67 | 66.6 | 78 | 5.7 |
| P-70 | 69.6 | 81 | 5.7 |
| P-71 | 70.6 | 82 | 5.7 |
| P-75 | 74.6 | 86 | 5.7 |
| P-80 | 79.6 | 91 | 5.7 |
| P-85 | 84.6 | 96 | 5.7 |
| P-90 | 89.6 | 101 | 5.7 |
| P-95 | 94.6 | 106 | 5.7 |
| P-100 | 99.6 | 111 | 5.7 |
| P-102 | 101.6 | 113 | 5.7 |
| P-105 | 104.6 | 116 | 5.7 |
| P-110 | 109.6 | 121 | 5.7 |

專業製造：橡膠 O 環、C 夾、迫緊、膜片、鐵氟龍、橡膠訂作規格外陸續開模中，請歡迎來電洽詢。

此規格材質 NBR90、VT、SE 若有需要需詢問。

O 環 AS-568 規格

AS-568-Type O-Ring Size List

| 材質 | 橡膠 | 橡膠(高壓) | 氟橡膠(耐熱) | 矽橡膠 |
|----|-------|--------|---------|-----|
| | NBR70 | NBR90 | VT | SE |

單位 unit : mm



| O 環 AS-568 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|------------------|------------|------------|---------|
| AS-001 | 0.74 | 2.78 | 1.02 |
| AS-002 | 1.07 | 3.61 | 1.27 |
| AS-003 | 1.42 | 4.48 | 1.53 |
| AS-004 | 1.78 | 5.34 | 1.78 |
| AS-005 | 2.57 | 6.13 | 1.78 |
| AS-006 | 2.9 | 6.46 | 1.78 |
| AS-007 | 3.69 | 7.25 | 1.78 |
| AS-008 | 4.47 | 8.03 | 1.78 |
| AS-009 | 5.29 | 8.85 | 1.78 |
| AS-010 | 6.07 | 9.63 | 1.78 |
| AS-011 | 7.65 | 11.21 | 1.78 |
| AS-012 | 9.25 | 12.81 | 1.78 |
| AS-013 | 10.82 | 14.38 | 1.78 |
| AS-014 | 12.42 | 15.98 | 1.78 |
| AS-015 | 14 | 17.56 | 1.78 |
| AS-016 | 15.6 | 19.16 | 1.78 |
| AS-017 | 17.17 | 20.73 | 1.78 |
| AS-018 | 18.77 | 22.33 | 1.78 |
| AS-019 | 20.35 | 23.91 | 1.78 |
| AS-020 | 21.95 | 25.51 | 1.78 |
| AS-021 | 23.52 | 27.08 | 1.78 |
| AS-022 | 25.12 | 28.68 | 1.78 |
| AS-023 | 26.7 | 30.26 | 1.78 |
| AS-024 | 28.3 | 31.86 | 1.78 |
| AS-025 | 29.87 | 33.43 | 1.78 |
| AS-026 | 31.47 | 35.03 | 1.78 |
| AS-027 | 33.05 | 36.61 | 1.78 |
| AS-028 | 34.65 | 38.21 | 1.78 |
| AS-029 | 37.82 | 41.38 | 1.78 |
| AS-030 | 41 | 44.56 | 1.78 |
| AS-031 | 44.17 | 47.73 | 1.78 |
| AS-032 | 47.35 | 50.91 | 1.78 |
| AS-033 | 50.52 | 54.08 | 1.78 |
| AS-034 | 53.7 | 57.26 | 1.78 |
| AS-035 | 56.87 | 60.43 | 1.78 |
| AS-036 | 60.04 | 63.6 | 1.78 |
| AS-037 | 63.22 | 66.78 | 1.78 |
| AS-038 | 66.4 | 69.96 | 1.78 |

| O 環 AS-568 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|------------------|------------|------------|---------|
| AS-039 | 69.57 | 73.13 | 1.78 |
| AS-040 | 72.75 | 76.31 | 1.78 |
| AS-041 | 75.92 | 79.48 | 1.78 |
| AS-042 | 82.27 | 85.83 | 1.78 |
| AS-043 | 88.62 | 92.18 | 1.78 |
| AS-044 | 94.97 | 98.53 | 1.78 |
| AS-045 | 101.32 | 104.88 | 1.78 |
| AS-046 | 107.62 | 111.18 | 1.78 |
| AS-047 | 114.02 | 117.58 | 1.78 |
| AS-048 | 120.37 | 123.93 | 1.78 |
| AS-049 | 126.72 | 130.28 | 1.78 |
| AS-050 | 133.07 | 136.63 | 1.78 |
| AS-102 | 1.24 | 6.48 | 2.62 |
| AS-103 | 2.05 | 7.29 | 2.62 |
| AS-104 | 2.84 | 8.08 | 2.62 |
| AS-105 | 3.63 | 8.87 | 2.62 |
| AS-106 | 4.42 | 9.66 | 2.62 |
| AS-107 | 5.23 | 10.47 | 2.62 |
| AS-108 | 6.02 | 11.26 | 2.62 |
| AS-109 | 7.6 | 12.84 | 2.62 |
| AS-110 | 9.19 | 14.43 | 2.62 |
| AS-111 | 10.77 | 16.01 | 2.62 |
| AS-112 | 12.37 | 17.61 | 2.62 |
| AS-113 | 13.95 | 19.19 | 2.62 |
| AS-114 | 15.54 | 20.78 | 2.62 |
| AS-115 | 17.12 | 22.36 | 2.62 |
| AS-116 | 18.72 | 23.96 | 2.62 |
| AS-117 | 20.29 | 25.53 | 2.62 |
| AS-118 | 21.9 | 27.14 | 2.62 |
| AS-119 | 23.47 | 28.71 | 2.62 |
| AS-120 | 25.07 | 30.31 | 2.62 |
| AS-121 | 26.65 | 31.89 | 2.62 |
| AS-122 | 28.25 | 33.49 | 2.62 |
| AS-123 | 29.82 | 35.06 | 2.62 |
| AS-124 | 31.42 | 36.66 | 2.62 |
| AS-125 | 32.99 | 38.23 | 2.62 |
| AS-126 | 34.6 | 39.84 | 2.62 |
| AS-127 | 36.17 | 41.41 | 2.62 |

專業製造：橡膠 O 環、C 型迫緊、膜片、鐵氟龍、橡膠訂作規格外陸續開模中，請歡迎來電洽詢。

O 環 AS-568 規格

AS-568-Type O-Ring Size List



單位 unit : mm

| 材質 | 橡膠 | 橡膠 (高壓) | 氟橡膠 (耐熱) | 矽橡膠 |
|----|-------|---------|----------|-----|
| | NBR70 | NBR90 | VT | SE |

| O 環 AS-568 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|------------------|------------|------------|---------|
| AS-128 | 37.77 | 43.01 | 2.62 |
| AS-129 | 39.35 | 44.59 | 2.62 |
| AS-130 | 40.95 | 46.19 | 2.62 |
| AS-131 | 42.52 | 47.76 | 2.62 |
| AS-132 | 44.12 | 49.36 | 2.62 |
| AS-133 | 45.7 | 50.94 | 2.62 |
| AS-134 | 47.3 | 52.54 | 2.62 |
| AS-135 | 48.9 | 54.14 | 2.62 |
| AS-136 | 50.47 | 55.71 | 2.62 |
| AS-137 | 52.07 | 57.31 | 2.62 |
| AS-138 | 53.65 | 58.89 | 2.62 |
| AS-139 | 55.25 | 60.49 | 2.62 |
| AS-140 | 56.82 | 62.06 | 2.62 |
| AS-141 | 58.42 | 63.66 | 2.62 |
| AS-142 | 60 | 65.24 | 2.62 |
| AS-143 | 61.6 | 66.84 | 2.62 |
| AS-144 | 63.17 | 68.41 | 2.62 |
| AS-145 | 64.77 | 70.01 | 2.62 |
| AS-146 | 66.35 | 71.59 | 2.62 |
| AS-147 | 67.95 | 73.19 | 2.62 |
| AS-148 | 69.52 | 74.76 | 2.62 |
| AS-149 | 71.12 | 76.36 | 2.62 |
| AS-150 | 72.7 | 77.94 | 2.62 |
| AS-151 | 75.87 | 81.11 | 2.62 |
| AS-152 | 82.22 | 87.46 | 2.62 |
| AS-153 | 88.57 | 93.81 | 2.62 |
| AS-154 | 94.92 | 100.16 | 2.62 |
| AS-155 | 101.27 | 106.51 | 2.62 |
| AS-156 | 107.62 | 112.86 | 2.62 |
| AS-157 | 113.97 | 119.21 | 2.62 |
| AS-158 | 120.32 | 125.56 | 2.62 |
| AS-159 | 126.67 | 131.91 | 2.62 |
| AS-160 | 133.02 | 138.26 | 2.62 |
| AS-161 | 139.37 | 144.61 | 2.62 |
| AS-162 | 145.72 | 150.96 | 2.62 |
| AS-163 | 152.07 | 157.31 | 2.62 |
| AS-164 | 158.42 | 163.66 | 2.62 |
| AS-165 | 164.77 | 170.01 | 2.62 |

| O 環 AS-568 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|------------------|------------|------------|---------|
| AS-166 | 171.12 | 176.36 | 2.62 |
| AS-167 | 177.47 | 182.71 | 2.62 |
| AS-168 | 183.82 | 189.06 | 2.62 |
| AS-169 | 190.17 | 195.41 | 2.62 |
| AS-170 | 196.52 | 201.76 | 2.62 |
| AS-171 | 202.87 | 208.11 | 2.62 |
| AS-172 | 209.22 | 214.46 | 2.62 |
| AS-173 | 215.57 | 220.81 | 2.62 |
| AS-174 | 221.92 | 227.16 | 2.62 |
| AS-175 | 228.27 | 233.51 | 2.62 |
| AS-176 | 234.62 | 239.86 | 2.62 |
| AS-177 | 240.97 | 246.21 | 2.62 |
| AS-178 | 247.32 | 252.56 | 2.62 |
| AS-201 | 4.34 | 11.4 | 3.53 |
| AS-202 | 5.94 | 13 | 3.53 |
| AS-203 | 7.52 | 14.58 | 3.53 |
| AS-204 | 9.12 | 16.18 | 3.53 |
| AS-205 | 10.69 | 17.75 | 3.53 |
| AS-206 | 12.29 | 19.35 | 3.53 |
| AS-207 | 13.87 | 20.93 | 3.53 |
| AS-208 | 15.47 | 22.53 | 3.53 |
| AS-209 | 17.04 | 24.1 | 3.53 |
| AS-210 | 18.64 | 25.7 | 3.53 |
| AS-211 | 20.22 | 27.28 | 3.53 |
| AS-212 | 21.82 | 28.88 | 3.53 |
| AS-213 | 23.4 | 30.46 | 3.53 |
| AS-214 | 25 | 32.06 | 3.53 |
| AS-215 | 26.57 | 33.63 | 3.53 |
| AS-216 | 28.17 | 35.23 | 3.53 |
| AS-217 | 29.75 | 36.81 | 3.53 |
| AS-218 | 31.34 | 38.4 | 3.53 |
| AS-219 | 32.92 | 39.98 | 3.53 |
| AS-220 | 34.52 | 41.58 | 3.53 |
| AS-221 | 36.1 | 43.16 | 3.53 |
| AS-222 | 37.7 | 44.76 | 3.53 |
| AS-223 | 40.87 | 47.93 | 3.53 |
| AS-224 | 44.05 | 51.11 | 3.53 |
| AS-225 | 47.22 | 54.28 | 3.53 |

專業製造：橡膠 O 環、C 形 O 環、C 形 O 環、迫緊、膜片、鐵氟龍、橡膠訂作規格外陸續開模中，請歡迎來電洽詢。

此規格材質 NBR90、VT、SE 若有需要需詢問。

O 環 AS-568 規格

AS-568-Type O-Ring Size List



中威密封元件

| 材質 | 橡膠 | 橡膠(高壓) | 氟橡膠(耐熱) | 矽橡膠 |
|----|-------|--------|---------|-----|
| | NBR70 | NBR90 | VT | SE |

單位 unit : mm

| O 環 AS-568 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|------------------|------------|------------|---------|
| AS-226 | 50.4 | 57.46 | 3.53 |
| AS-227 | 53.57 | 60.63 | 3.53 |
| AS-228 | 56.75 | 63.81 | 3.53 |
| AS-229 | 59.92 | 66.98 | 3.53 |
| AS-230 | 63.1 | 70.16 | 3.53 |
| AS-231 | 66.27 | 73.33 | 3.53 |
| AS-232 | 69.44 | 76.5 | 3.53 |
| AS-233 | 72.62 | 79.68 | 3.53 |
| AS-234 | 75.79 | 82.85 | 3.53 |
| AS-235 | 78.97 | 86.03 | 3.53 |
| AS-236 | 82.14 | 89.2 | 3.53 |
| AS-237 | 85.32 | 92.38 | 3.53 |
| AS-238 | 88.49 | 95.55 | 3.53 |
| AS-239 | 91.67 | 98.73 | 3.53 |
| AS-240 | 94.84 | 101.9 | 3.53 |
| AS-241 | 98.02 | 105.08 | 3.53 |
| AS-242 | 101.19 | 108.25 | 3.53 |
| AS-243 | 104.37 | 111.43 | 3.53 |
| AS-244 | 107.54 | 114.6 | 3.53 |
| AS-245 | 110.72 | 117.78 | 3.53 |
| AS-246 | 113.89 | 120.95 | 3.53 |
| AS-247 | 117.07 | 124.13 | 3.53 |
| AS-248 | 120.24 | 127.3 | 3.53 |
| AS-249 | 123.42 | 130.48 | 3.53 |
| AS-250 | 126.59 | 133.65 | 3.53 |
| AS-251 | 129.77 | 136.83 | 3.53 |
| AS-252 | 132.94 | 140 | 3.53 |
| AS-253 | 136.12 | 143.18 | 3.53 |
| AS-254 | 139.3 | 146.36 | 3.53 |
| AS-255 | 142.47 | 149.53 | 3.53 |
| AS-256 | 145.65 | 152.71 | 3.53 |
| AS-257 | 148.82 | 155.88 | 3.53 |
| AS-258 | 152 | 159.06 | 3.53 |
| AS-259 | 158.35 | 165.41 | 3.53 |
| AS-260 | 164.7 | 171.76 | 3.53 |
| AS-261 | 171.05 | 178.11 | 3.53 |
| AS-262 | 177.4 | 184.46 | 3.53 |
| AS-263 | 183.75 | 190.81 | 3.53 |



| O 環 AS-568 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|------------------|------------|------------|---------|
| AS-264 | 190.1 | 197.16 | 3.53 |
| AS-265 | 196.45 | 203.51 | 3.53 |
| AS-266 | 202.8 | 209.86 | 3.53 |
| AS-267 | 209.15 | 216.21 | 3.53 |
| AS-268 | 215.5 | 222.56 | 3.53 |
| AS-269 | 221.85 | 228.91 | 3.53 |
| AS-270 | 228.2 | 235.26 | 3.53 |
| AS-271 | 234.55 | 241.61 | 3.53 |
| AS-272 | 240.9 | 247.96 | 3.53 |
| AS-273 | 247.25 | 254.31 | 3.53 |
| AS-274 | 253.6 | 260.66 | 3.53 |
| AS-275 | 266.3 | 273.36 | 3.53 |
| AS-276 | 279 | 286.06 | 3.53 |
| AS-277 | 291.7 | 298.76 | 3.53 |
| AS-278 | 304.4 | 311.46 | 3.53 |
| AS-279 | 329.8 | 336.86 | 3.53 |
| AS-280 | 355.2 | 362.26 | 3.53 |
| AS-281 | 380.6 | 387.66 | 3.53 |
| AS-282 | 405.26 | 412.32 | 3.53 |
| AS-283 | 430.66 | 437.72 | 3.53 |
| AS-284 | 456.06 | 463.12 | 3.53 |
| AS-309 | 10.46 | 21.12 | 5.33 |
| AS-310 | 12.07 | 22.73 | 5.33 |
| AS-311 | 13.64 | 24.3 | 5.33 |
| AS-312 | 15.24 | 25.9 | 5.33 |
| AS-313 | 16.81 | 27.47 | 5.33 |
| AS-314 | 18.42 | 29.08 | 5.33 |
| AS-315 | 19.99 | 30.65 | 5.33 |
| AS-316 | 21.59 | 32.25 | 5.33 |
| AS-317 | 23.16 | 33.82 | 5.33 |
| AS-318 | 24.77 | 35.43 | 5.33 |
| AS-319 | 26.34 | 37 | 5.33 |
| AS-320 | 27.94 | 38.6 | 5.33 |
| AS-321 | 29.51 | 40.17 | 5.33 |
| AS-322 | 31.12 | 41.78 | 5.33 |
| AS-323 | 32.69 | 43.35 | 5.33 |
| AS-324 | 34.29 | 44.95 | 5.33 |
| AS-325 | 37.47 | 48.13 | 5.33 |

專業製造：橡膠 O 環、C 型迫緊、膜片、鐵氟龍、橡膠訂作規格外陸續開模中，請歡迎來電洽詢。

此規格材質 NBR90、VT、SE 若有需要需詢問。

O 環 AS-568 規格

AS-568-Type O-Ring Size List



單位 unit : mm

| 材質 | 橡膠 | 橡膠 (高壓) | 氟橡膠 (耐熱) | 矽橡膠 |
|----|-------|---------|----------|-----|
| | NBR70 | NBR90 | VT | SE |

| O 環 AS-568 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|---------------|---------|---------|------|
| AS-326 | 40.65 | 51.31 | 5.33 |
| AS-327 | 43.82 | 54.48 | 5.33 |
| AS-328 | 46.99 | 57.65 | 5.33 |
| AS-329 | 50.16 | 60.82 | 5.33 |
| AS-330 | 53.34 | 64 | 5.33 |
| AS-331 | 56.52 | 67.18 | 5.33 |
| AS-332 | 59.69 | 70.35 | 5.33 |
| AS-333 | 62.87 | 73.53 | 5.33 |
| AS-334 | 66.04 | 76.7 | 5.33 |
| AS-335 | 69.22 | 79.88 | 5.33 |
| AS-336 | 72.39 | 83.05 | 5.33 |
| AS-337 | 75.57 | 86.23 | 5.33 |
| AS-338 | 78.74 | 89.4 | 5.33 |
| AS-339 | 81.92 | 92.58 | 5.33 |
| AS-340 | 85.09 | 95.75 | 5.33 |
| AS-341 | 88.27 | 98.93 | 5.33 |
| AS-342 | 91.44 | 102.1 | 5.33 |
| AS-343 | 94.62 | 105.28 | 5.33 |
| AS-344 | 97.79 | 108.45 | 5.33 |
| AS-345 | 100.96 | 111.62 | 5.33 |
| AS-346 | 104.14 | 114.8 | 5.33 |
| AS-347 | 107.32 | 117.98 | 5.33 |
| AS-348 | 110.49 | 121.15 | 5.33 |
| AS-349 | 113.67 | 124.33 | 5.33 |
| AS-350 | 116.84 | 127.5 | 5.33 |
| AS-351 | 120.02 | 130.68 | 5.33 |
| AS-352 | 123.19 | 133.85 | 5.33 |
| AS-353 | 126.37 | 137.03 | 5.33 |
| AS-354 | 129.54 | 140.2 | 5.33 |
| AS-355 | 132.72 | 143.38 | 5.33 |
| AS-356 | 135.89 | 146.55 | 5.33 |
| AS-357 | 139.07 | 149.73 | 5.33 |
| AS-358 | 142.24 | 152.9 | 5.33 |
| AS-359 | 145.42 | 156.08 | 5.33 |
| AS-360 | 148.59 | 159.25 | 5.33 |
| AS-361 | 151.77 | 162.43 | 5.33 |
| AS-362 | 158.12 | 168.78 | 5.33 |
| AS-363 | 164.47 | 175.13 | 5.33 |

| O 環 AS-568 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|---------------|---------|---------|------|
| AS-364 | 170.82 | 181.48 | 5.33 |
| AS-365 | 177.17 | 187.83 | 5.33 |
| AS-366 | 183.52 | 194.18 | 5.33 |
| AS-367 | 189.87 | 200.53 | 5.33 |
| AS-368 | 196.22 | 206.88 | 5.33 |
| AS-369 | 202.57 | 213.23 | 5.33 |
| AS-370 | 208.92 | 219.58 | 5.33 |
| AS-371 | 215.27 | 225.93 | 5.33 |
| AS-372 | 221.62 | 232.28 | 5.33 |
| AS-373 | 227.97 | 238.63 | 5.33 |
| AS-374 | 234.32 | 244.98 | 5.33 |
| AS-375 | 240.67 | 251.33 | 5.33 |
| AS-376 | 247.02 | 257.68 | 5.33 |
| AS-377 | 253.37 | 264.03 | 5.33 |
| AS-378 | 266.07 | 276.73 | 5.33 |
| AS-379 | 278.77 | 289.43 | 5.33 |
| AS-380 | 291.47 | 302.13 | 5.33 |
| AS-381 | 304.17 | 314.83 | 5.33 |
| AS-382 | 329.55 | 340.21 | 5.33 |
| AS-383 | 354.97 | 365.63 | 5.33 |
| AS-384 | 380.37 | 391.03 | 5.33 |
| AS-385 | 405.26 | 415.92 | 5.33 |
| AS-386 | 430.65 | 441.31 | 5.33 |
| AS-387 | 456.06 | 466.72 | 5.33 |
| AS-388 | 481.46 | 492.12 | 5.33 |
| AS-389 | 506.86 | 517.52 | 5.33 |
| AS-390 | 532.26 | 542.92 | 5.33 |
| AS-391 | 557.66 | 568.32 | 5.33 |
| AS-392 | 582.65 | 593.31 | 5.33 |
| AS-393 | 608.1 | 618.76 | 5.33 |
| AS-394 | 633.5 | 644.16 | 5.33 |
| AS-395 | 658.85 | 669.51 | 5.33 |
| AS-401 | 58 | 72 | 7 |
| AS-402 | 64 | 78 | 7 |
| AS-403 | 68 | 82 | 7 |
| AS-404 | 73 | 87 | 7 |
| AS-405 | 79 | 93 | 7 |
| AS-406 | 83 | 97 | 7 |

專業製造：橡膠 O 環、C 形 O 環、迫緊、膜片、鐵氟龍、橡膠訂作規格外陸續開模中，請歡迎來電洽詢。

此規格材質 NBR90、VT、SE 若有需要需詢問。

O 環 AS-568 規格

AS-568-Type O-Ring Size List



中威密封元件

| 材質 | 橡膠 | 橡膠(高壓) | 氟橡膠(耐熱) | 矽橡膠 |
|----|-------|--------|---------|-----|
| | NBR70 | NBR90 | VT | SE |

單位 unit : mm

| O 環 AS-568 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|------------------|------------|------------|---------|
| AS-407 | 89 | 103 | 7 |
| AS-408 | 94 | 108 | 7 |
| AS-409 | 99 | 113 | 7 |
| AS-410 | 101 | 115 | 7 |
| AS-411 | 106 | 120 | 7 |
| AS-425 | 113.67 | 127.65 | 6.99 |
| AS-426 | 116.84 | 130.82 | 6.99 |
| AS-427 | 120.02 | 134 | 6.99 |
| AS-428 | 123.19 | 137.17 | 6.99 |
| AS-429 | 126.37 | 140.35 | 6.99 |
| AS-430 | 129.54 | 143.52 | 6.99 |
| AS-431 | 132.72 | 146.7 | 6.99 |
| AS-432 | 135.89 | 149.87 | 6.99 |
| AS-433 | 139.07 | 153.05 | 6.99 |
| AS-434 | 142.24 | 156.22 | 6.99 |
| AS-435 | 145.42 | 159.4 | 6.99 |
| AS-436 | 148.59 | 162.57 | 6.99 |
| AS-437 | 151.77 | 165.75 | 6.99 |
| AS-438 | 158.12 | 172.1 | 6.99 |
| AS-439 | 164.47 | 178.45 | 6.99 |
| AS-440 | 170.82 | 184.8 | 6.99 |
| AS-441 | 177.17 | 191.15 | 6.99 |
| AS-442 | 183.52 | 197.5 | 6.99 |
| AS-443 | 189.87 | 203.85 | 6.99 |
| AS-444 | 196.22 | 210.2 | 6.99 |
| AS-445 | 202.57 | 216.55 | 6.99 |
| AS-446 | 215.27 | 229.25 | 6.99 |
| AS-447 | 227.97 | 241.95 | 6.99 |
| AS-448 | 240.67 | 254.65 | 6.99 |
| AS-449 | 253.37 | 267.35 | 6.99 |
| AS-450 | 266.07 | 280.05 | 6.99 |
| AS-451 | 278.77 | 292.75 | 6.99 |
| AS-452 | 291.47 | 305.45 | 6.99 |
| AS-453 | 304.17 | 318.15 | 6.99 |
| AS-454 | 316.87 | 330.85 | 6.99 |
| AS-455 | 329.57 | 343.55 | 6.99 |
| AS-456 | 342.27 | 356.25 | 6.99 |
| AS-457 | 354.97 | 368.95 | 6.99 |



| O 環 AS-568 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|------------------|------------|------------|---------|
| AS-458 | 367.67 | 381.65 | 6.99 |
| AS-459 | 380.37 | 394.35 | 6.99 |
| AS-460 | 393.07 | 407.05 | 6.99 |
| AS-461 | 405.26 | 419.24 | 6.99 |
| AS-462 | 417.96 | 431.94 | 6.99 |
| AS-463 | 430.66 | 444.64 | 6.99 |
| AS-464 | 443.36 | 457.34 | 6.99 |
| AS-465 | 456.06 | 470.04 | 6.99 |
| AS-466 | 468.76 | 482.74 | 6.99 |
| AS-467 | 481.46 | 495.44 | 6.99 |
| AS-468 | 494.16 | 508.14 | 6.99 |
| AS-469 | 506.86 | 520.84 | 6.99 |
| AS-470 | 532.26 | 546.24 | 6.99 |
| AS-471 | 557.66 | 571.64 | 6.99 |
| AS-472 | 582.65 | 596.63 | 6.99 |
| AS-473 | 608.1 | 622.08 | 6.99 |
| AS-474 | 633.5 | 647.48 | 6.99 |
| AS-475 | 658.85 | 672.83 | 6.99 |
| AS-901 | 4.7 | 7.54 | 1.42 |
| AS-902 | 6.07 | 9.33 | 1.63 |
| AS-903 | 7.65 | 10.91 | 1.63 |
| AS-904 | 8.92 | 12.58 | 1.83 |
| AS-905 | 10.52 | 14.18 | 1.83 |
| AS-906 | 11.89 | 15.85 | 1.98 |
| AS-907 | 13.46 | 17.62 | 2.08 |
| AS-908 | 16.36 | 20.78 | 2.21 |
| AS-909 | 17.94 | 22.86 | 2.46 |
| AS-910 | 19.18 | 24.1 | 2.46 |
| AS-911 | 21.92 | 27.82 | 2.95 |
| AS-912 | 23.47 | 29.37 | 2.95 |
| AS-913 | 25.04 | 30.94 | 2.95 |
| AS-914 | 26.6 | 32.5 | 2.95 |
| AS-916 | 29.75 | 35.65 | 2.95 |
| AS-918 | 34.42 | 40.32 | 2.95 |
| AS-920 | 37.46 | 43.46 | 3 |
| AS-924 | 43.68 | 49.68 | 3 |
| AS-928 | 53.09 | 59.09 | 3 |
| AS-932 | 59.36 | 65.36 | 3 |

專業製造：橡膠 O 環、C 型 O 環、膜片、鐵氟龍、橡膠訂作規格外陸續開模中，請歡迎來電洽詢。

此規格材質 NBR90、VT、SE 若有需要需詢問。

O 環 S 規格

S-Type O-Ring Size List



單位 unit : mm

| 材質 | 橡膠 | 橡膠 (高壓) | 氟橡膠 (耐熱) | 矽橡膠 |
|----|-------|---------|----------|-----|
| | NBR70 | NBR90 | VT | SE |

| O 環 S 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|----------|---------|---------|------|
| S-002 | 1.5 | 4.5 | 1.5 |
| S-003 | 2.5 | 5.5 | 1.5 |
| S-004 | 3.5 | 6.5 | 1.5 |
| S-005 | 4.5 | 7.5 | 1.5 |
| S-006 | 5.5 | 8.5 | 1.5 |
| S-007 | 6.5 | 9.5 | 1.5 |
| S-008 | 7.5 | 10.5 | 1.5 |
| S-009 | 8.5 | 11.5 | 1.5 |
| S-010 | 9.5 | 12.5 | 1.5 |
| S-11.2 | 10.7 | 13.7 | 1.5 |
| S-012 | 11.5 | 14.5 | 1.5 |
| S-12.5 | 12 | 15 | 1.5 |
| S-014 | 13.5 | 16.5 | 1.5 |
| S-015 | 14.5 | 17.5 | 1.5 |
| S-016 | 15.5 | 18.5 | 1.5 |
| S-018 | 17.5 | 20.5 | 1.5 |
| S-020 | 19.5 | 22.5 | 1.5 |
| S-022 | 21.5 | 24.5 | 1.5 |
| S-22.4 | 21.9 | 25.9 | 2 |
| S-024 | 23.5 | 27.5 | 2 |
| S-025 | 24.5 | 28.5 | 2 |
| S-026 | 25.5 | 29.5 | 2 |
| S-027 | 26.5 | 30.5 | 2 |
| S-028 | 27.5 | 31.5 | 2 |
| S-029 | 28.5 | 32.5 | 2 |
| S-030 | 29.5 | 33.5 | 2 |
| S-31.5 | 31 | 35 | 2 |
| S-032 | 31.5 | 35.5 | 2 |
| S-034 | 33.5 | 37.5 | 2 |
| S-035 | 34.5 | 38.5 | 2 |
| S-35.5 | 35 | 39 | 2 |
| S-036 | 35.5 | 39.5 | 2 |
| S-037 | 36.5 | 40.5 | 2 |
| S-038 | 37.5 | 41.5 | 2 |
| S-039 | 38.5 | 42.5 | 2 |
| S-040 | 39.5 | 43.5 | 2 |
| S-042 | 41.5 | 45.5 | 2 |



| O 環 S 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|----------|---------|---------|------|
| S-044 | 43.5 | 47.5 | 2 |
| S-045 | 44.5 | 48.5 | 2 |
| S-046 | 45.5 | 49.5 | 2 |
| S-048 | 47.5 | 51.5 | 2 |
| S-050 | 49.5 | 53.5 | 2 |
| S-053 | 52.5 | 56.5 | 2 |
| S-055 | 54.5 | 58.5 | 2 |
| S-056 | 55.5 | 59.5 | 2 |
| S-060 | 59.5 | 63.5 | 2 |
| S-063 | 62.5 | 66.5 | 2 |
| S-065 | 64.5 | 68.5 | 2 |
| S-067 | 66.5 | 70.5 | 2 |
| S-070 | 69.5 | 73.5 | 2 |
| S-071 | 70.5 | 74.5 | 2 |
| S-075 | 74.5 | 78.5 | 2 |
| S-080 | 79.5 | 83.5 | 2 |
| S-085 | 84.5 | 88.5 | 2 |
| S-090 | 89.5 | 93.5 | 2 |
| S-095 | 94.5 | 98.5 | 2 |
| S-100 | 99.5 | 103.5 | 2 |
| S-105 | 104.5 | 108.5 | 2 |
| S-110 | 109.5 | 113.5 | 2 |
| S-112 | 111.5 | 115.5 | 2 |
| S-115 | 114.5 | 118.5 | 2 |
| S-120 | 119.5 | 123.5 | 2 |
| S-125 | 124.5 | 128.5 | 2 |
| S-130 | 129.5 | 133.5 | 2 |
| S-132 | 131.5 | 135.5 | 2 |
| S-135 | 134.5 | 138.5 | 2 |
| S-140 | 139.5 | 143.5 | 2 |
| S-145 | 144.5 | 148.5 | 2 |
| S-150 | 149.5 | 153.5 | 2 |
| S-155 | 154.5 | 158.5 | 2 |
| S-160 | 159.5 | 163.5 | 2 |
| S-165 | 164.5 | 168.5 | 2 |
| S-170 | 169.5 | 173.5 | 2 |
| S-175 | 174.5 | 178.5 | 2 |

專業製造：橡膠 O 環、C 型 O 環、迫緊、膜片、鐵氟龍、橡膠訂作規格外陸續開模中，請歡迎來電洽詢。

此規格材質 NBR90、VT、SE 若有需要需詢問。

O 環 V 規格

V-Type O-Ring Size List



單位 unit : mm

| 材質 | 橡膠 | 橡膠 (高壓) | 氟橡膠 (耐熱) | 矽橡膠 |
|----|-------|---------|----------|-----|
| | NBR70 | NBR90 | VT | SE |

| O 環 V 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|----------|---------|---------|------|
| V-85 | 84 | 92 | 4 |
| V-90 | 89 | 97 | 4 |
| V-95 | 94 | 102 | 4 |
| V-100 | 99 | 107 | 4 |
| V-105 | 104 | 112 | 4 |
| V-110 | 109 | 117 | 4 |
| V-115 | 114 | 122 | 4 |
| V-120 | 119 | 127 | 4 |
| V-125 | 124 | 132 | 4 |
| V-130 | 129 | 137 | 4 |
| V-135 | 134 | 142 | 4 |
| V-140 | 138.5 | 146.5 | 4 |
| V-145 | 143.5 | 151.5 | 4 |
| V-150 | 148.5 | 156.5 | 4 |
| V-155 | 153 | 161 | 4 |
| V-160 | 158 | 166 | 4 |
| V-170 | 168 | 176 | 4 |
| V-175 | 173 | 181 | 4 |
| V-180 | 178 | 186 | 4 |
| V-185 | 183 | 191 | 4 |
| V-190 | 188 | 196 | 4 |
| V-195 | 193 | 201 | 4 |
| V-200 | 198 | 206 | 4 |
| V-205 | 203 | 211 | 4 |
| V-210 | 208 | 216 | 4 |
| V-215 | 213 | 221 | 4 |
| V-220 | 218 | 226 | 4 |
| V-225 | 222.5 | 234.5 | 6 |
| V-230 | 227.5 | 239.5 | 6 |
| V-235 | 232.5 | 244.5 | 6 |
| V-240 | 237.5 | 249.5 | 6 |
| V-245 | 242.5 | 254.5 | 6 |
| V-250 | 247.5 | 259.5 | 6 |
| V-255 | 252.5 | 264.5 | 6 |
| V-260 | 257.5 | 269.5 | 6 |
| V-265 | 262.5 | 274.5 | 6 |
| V-270 | 267.5 | 279.5 | 6 |
| V-275 | 272 | 284 | 6 |



| O 環 V 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|----------|---------|---------|------|
| V-280 | 277 | 289 | 6 |
| V-285 | 282 | 294 | 6 |
| V-290 | 287 | 299 | 6 |
| V-295 | 292 | 304 | 6 |
| V-300 | 297 | 309 | 6 |
| V-305 | 302 | 314 | 6 |
| V-310 | 307 | 319 | 6 |
| V-315 | 312 | 324 | 6 |
| V-320 | 317 | 329 | 6 |
| V-325 | 321.5 | 333.5 | 6 |
| V-330 | 326.5 | 338.5 | 6 |
| V-335 | 331.5 | 343.5 | 6 |
| V-340 | 336.5 | 348.5 | 6 |
| V-345 | 341.5 | 353.5 | 6 |
| V-350 | 346.5 | 358.5 | 6 |
| V-355 | 351.5 | 363.5 | 6 |
| V-360 | 356.5 | 368.5 | 6 |
| V-365 | 361.5 | 373.5 | 6 |
| V-370 | 366.5 | 378.5 | 6 |
| V-375 | 371.5 | 383.5 | 6 |
| V-380 | 376 | 388 | 6 |
| V-385 | 381 | 393 | 6 |
| V-390 | 386 | 398 | 6 |
| V-395 | 391 | 403 | 6 |
| V-400 | 396 | 408 | 6 |
| V-405 | 401 | 413 | 6 |
| V-410 | 406 | 418 | 6 |
| V-415 | 411 | 423 | 6 |
| V-420 | 416 | 428 | 6 |
| V-425 | 421 | 433 | 6 |
| V-430 | 425.5 | 437.5 | 6 |
| V-435 | 430.5 | 442.5 | 6 |
| V-445 | 440.5 | 452.5 | 6 |
| V-450 | 445.5 | 457.5 | 6 |
| V-455 | 450.5 | 462.5 | 6 |
| V-460 | 455.5 | 467.5 | 6 |
| V-465 | 460.5 | 472.5 | 6 |
| V-470 | 465.5 | 477.5 | 6 |

專業製造：橡膠 O 環、C 夾、迫緊、膜片、鐵氟龍、橡膠訂作規格外陸續開模中，請歡迎來電洽詢。

此規格材質 NBR90、VT、SE 若有需要需詢問。

O 環線徑 2mm 規格

Metric-Type O-Ring Size List



單位 unit : mm

| 材質 | 橡膠 | 橡膠 (高壓) | 氟橡膠 (耐熱) | 矽橡膠 |
|----|-------|---------|----------|-----|
| | NBR70 | NBR90 | VT | SE |



| O 環 線徑 2mm 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|------------------|------------|------------|---------|
| 2002 | 2 | 6 | 2 |
| 2003 | 3 | 7 | 2 |
| 2004 | 4 | 8 | 2 |
| 2005 | 5 | 9 | 2 |
| 2006 | 6 | 10 | 2 |
| 2007 | 7 | 11 | 2 |
| 2008 | 8 | 12 | 2 |
| 2009 | 9 | 13 | 2 |
| 2010 | 10 | 14 | 2 |
| 2011 | 11 | 15 | 2 |
| 2012 | 12 | 16 | 2 |
| 2013 | 13 | 17 | 2 |
| 2014 | 14 | 18 | 2 |
| 2015 | 15 | 19 | 2 |
| 2016 | 16 | 20 | 2 |
| 2017 | 17 | 21 | 2 |
| 2018 | 18 | 22 | 2 |
| 2019 | 19 | 23 | 2 |
| 2020 | 20 | 24 | 2 |
| 2021 | 21 | 25 | 2 |
| 2022 | 22 | 26 | 2 |
| 2023 | 23 | 27 | 2 |
| 2024 | 24 | 28 | 2 |
| 2025 | 25 | 29 | 2 |
| 2026 | 26 | 30 | 2 |
| 2027 | 27 | 31 | 2 |
| 2028 | 28 | 32 | 2 |
| 2029 | 29 | 33 | 2 |
| 2030 | 30 | 34 | 2 |
| 2031 | 31 | 35 | 2 |
| 2032 | 32 | 36 | 2 |
| 2033 | 33 | 37 | 2 |
| 2034 | 34 | 38 | 2 |
| 2035 | 35 | 39 | 2 |
| 2035.5 | 35.5 | 39.5 | 2 |
| 2036 | 36 | 40 | 2 |
| 2037 | 37 | 41 | 2 |

| O 環 線徑 2mm 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|------------------|------------|------------|---------|
| 2038 | 38 | 42 | 2 |
| 2039 | 39 | 43 | 2 |
| 2040 | 40 | 44 | 2 |
| 2042 | 42 | 46 | 2 |
| 2043 | 43 | 47 | 2 |
| 2044 | 44 | 48 | 2 |
| 2045 | 45 | 49 | 2 |
| 2046 | 46 | 50 | 2 |
| 2047 | 47 | 51 | 2 |
| 2048 | 48 | 52 | 2 |
| 2050 | 50 | 54 | 2 |
| 2052 | 52 | 56 | 2 |
| 2053 | 53 | 57 | 2 |
| 2055 | 55 | 59 | 2 |
| 2056 | 56 | 60 | 2 |
| 2057 | 57 | 61 | 2 |
| 2058 | 58 | 62 | 2 |
| 2059 | 59 | 63 | 2 |
| 2060 | 60 | 64 | 2 |
| 2061 | 61 | 65 | 2 |
| 2062 | 62 | 66 | 2 |
| 2063 | 63 | 67 | 2 |
| 2065 | 65 | 69 | 2 |
| 2068 | 68 | 72 | 2 |
| 2070 | 70 | 74 | 2 |
| 2071 | 71 | 75 | 2 |
| 2072 | 72 | 76 | 2 |
| 2073 | 73 | 77 | 2 |
| 2075 | 75 | 79 | 2 |
| 2076 | 76 | 80 | 2 |
| 2077 | 77 | 81 | 2 |
| 2078 | 78 | 82 | 2 |
| 2080 | 80 | 84 | 2 |
| 2085 | 85 | 89 | 2 |
| 2088 | 88 | 92 | 2 |
| 2090 | 90 | 94 | 2 |
| 2095 | 95 | 99 | 2 |

專業製造：橡膠 O 環、C 型迫緊、膜片、鐵氟龍、橡膠訂作規格外陸續開模中，請歡迎來電洽詢。

O 環線徑 3mm 規格

Metric-Type O-Ring Size List



單位 unit : mm

| 材質 | 橡膠 | 橡膠 (高壓) | 氟橡膠 (耐熱) | 矽橡膠 |
|----|-------|---------|----------|-----|
| | NBR70 | NBR90 | VT | SE |

| O 環 線徑 3mm 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|------------------|------------|------------|---------|
| 3004 | 4 | 10 | 3 |
| 3005 | 5 | 11 | 3 |
| 3006 | 6 | 12 | 3 |
| 3007 | 7 | 13 | 3 |
| 3008 | 8 | 14 | 3 |
| 3009 | 9 | 15 | 3 |
| 3010 | 10 | 16 | 3 |
| 3011 | 11 | 17 | 3 |
| 3012 | 12 | 18 | 3 |
| 3013 | 13 | 19 | 3 |
| 3014 | 14 | 20 | 3 |
| 3015 | 15 | 21 | 3 |
| 3016 | 16 | 22 | 3 |
| 3017 | 17 | 23 | 3 |
| 3018 | 18 | 24 | 3 |
| 3019 | 19 | 25 | 3 |
| 3020 | 20 | 26 | 3 |
| 3021 | 21 | 27 | 3 |
| 3022 | 22 | 28 | 3 |
| 3023 | 23 | 29 | 3 |
| 3024 | 24 | 30 | 3 |
| 3025 | 25 | 31 | 3 |
| 3026 | 26 | 32 | 3 |
| 3027 | 27 | 33 | 3 |
| 3028 | 28 | 34 | 3 |
| 3029 | 29 | 35 | 3 |
| 3030 | 30 | 36 | 3 |
| 3032 | 32 | 38 | 3 |
| 3033 | 33 | 39 | 3 |
| 3034 | 34 | 40 | 3 |
| 3035 | 35 | 41 | 3 |
| 3036 | 36 | 42 | 3 |
| 3037 | 37 | 43 | 3 |
| 3038 | 38 | 44 | 3 |
| 3040 | 40 | 46 | 3 |
| 3042 | 42 | 48 | 3 |
| 3043 | 43 | 49 | 3 |



| O 環 線徑 3mm 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|------------------|------------|------------|---------|
| 3045 | 45 | 51 | 3 |
| 3047 | 47 | 53 | 3 |
| 3048 | 48 | 54 | 3 |
| 3050 | 50 | 56 | 3 |
| 3051 | 51 | 57 | 3 |
| 3052 | 52 | 58 | 3 |
| 3053 | 53 | 59 | 3 |
| 3055 | 55 | 61 | 3 |
| 3056 | 56 | 62 | 3 |
| 3058 | 58 | 64 | 3 |
| 3060 | 60 | 66 | 3 |
| 3062 | 62 | 68 | 3 |
| 3063 | 63 | 69 | 3 |
| 3065 | 65 | 71 | 3 |
| 3067 | 67 | 73 | 3 |
| 3068 | 68 | 74 | 3 |
| 3070 | 70 | 76 | 3 |
| 3072 | 72 | 78 | 3 |
| 3075 | 75 | 81 | 3 |
| 3078 | 78 | 84 | 3 |
| 3080 | 80 | 86 | 3 |
| 3082 | 82 | 88 | 3 |
| 3085 | 85 | 91 | 3 |
| 3088 | 88 | 94 | 3 |
| 3090 | 90 | 96 | 3 |
| 3092 | 92 | 98 | 3 |
| 3095 | 95 | 101 | 3 |
| 3098 | 98 | 104 | 3 |
| 3100 | 100 | 106 | 3 |
| 3102 | 102 | 108 | 3 |
| 3105 | 105 | 111 | 3 |
| 3108 | 108 | 114 | 3 |
| 3110 | 110 | 116 | 3 |
| 3112 | 112 | 118 | 3 |
| 3115 | 115 | 121 | 3 |
| 3118 | 118 | 124 | 3 |
| 3120 | 120 | 126 | 3 |

專業製造：橡膠 O 環、C 型 O 環、迫緊、膜片、鐵氟龍、橡膠訂作規格外陸續開模中，請歡迎來電洽詢。

此規格材質 NBR90、VT、SE 若有需要需詢問。

O 環線徑 4mm 規格

Metric-Type O-Ring Size List



單位 unit : mm

| 材質 | 橡膠 | 橡膠 (高壓) | 氟橡膠 (耐熱) | 矽橡膠 |
|----|-------|---------|----------|-----|
| | NBR70 | NBR90 | VT | SE |



| O 環 線徑 4mm 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|------------------|------------|------------|---------|
| 4006 | 6 | 14 | 4 |
| 4008 | 8 | 16 | 4 |
| 4010 | 10 | 18 | 4 |
| 4011 | 11 | 19 | 4 |
| 4012 | 12 | 20 | 4 |
| 4013 | 13 | 21 | 4 |
| 4014 | 14 | 22 | 4 |
| 4015 | 15 | 23 | 4 |
| 4016 | 16 | 24 | 4 |
| 4017 | 17 | 25 | 4 |
| 4018 | 18 | 26 | 4 |
| 4019 | 19 | 27 | 4 |
| 4020 | 20 | 28 | 4 |
| 4021 | 21 | 29 | 4 |
| 4022 | 22 | 30 | 4 |
| 4024 | 24 | 32 | 4 |
| 4025 | 25 | 33 | 4 |
| 4026 | 26 | 34 | 4 |
| 4027 | 27 | 35 | 4 |
| 4028 | 28 | 36 | 4 |
| 4030 | 30 | 38 | 4 |
| 4032 | 32 | 40 | 4 |
| 4033 | 33 | 41 | 4 |
| 4034 | 34 | 42 | 4 |
| 4035 | 35 | 43 | 4 |
| 4036 | 36 | 44 | 4 |
| 4037 | 37 | 45 | 4 |
| 4038 | 38 | 46 | 4 |
| 4040 | 40 | 48 | 4 |
| 4041 | 41 | 49 | 4 |
| 4042 | 42 | 50 | 4 |
| 4043 | 43 | 51 | 4 |
| 4044 | 44 | 52 | 4 |
| 4045 | 45 | 53 | 4 |
| 4046 | 46 | 54 | 4 |
| 4047 | 47 | 55 | 4 |

| O 環 線徑 4mm 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|------------------|------------|------------|---------|
| 4048 | 48 | 56 | 4 |
| 4050 | 50 | 58 | 4 |
| 4051 | 51 | 59 | 4 |
| 4052 | 52 | 60 | 4 |
| 4054 | 54 | 62 | 4 |
| 4055 | 55 | 63 | 4 |
| 4056 | 56 | 64 | 4 |
| 4058 | 58 | 66 | 4 |
| 4060 | 60 | 68 | 4 |
| 4062 | 62 | 70 | 4 |
| 4064 | 64 | 72 | 4 |
| 4065 | 65 | 73 | 4 |
| 4068 | 68 | 76 | 4 |
| 4070 | 70 | 78 | 4 |
| 4072 | 72 | 80 | 4 |
| 4074 | 74 | 82 | 4 |
| 4075 | 75 | 83 | 4 |
| 4078 | 78 | 86 | 4 |
| 4080 | 80 | 88 | 4 |
| 4081 | 81 | 89 | 4 |
| 4082 | 82 | 90 | 4 |
| 4084 | 84 | 92 | 4 |
| 4085 | 85 | 93 | 4 |
| 4088 | 88 | 96 | 4 |
| 4090 | 90 | 98 | 4 |
| 4092 | 92 | 100 | 4 |
| 4095 | 95 | 103 | 4 |
| 4098 | 98 | 106 | 4 |
| 4099 | 99 | 107 | 4 |
| 4100 | 100 | 108 | 4 |
| 4102 | 102 | 110 | 4 |
| 4104 | 104 | 112 | 4 |
| 4105 | 105 | 113 | 4 |
| 4108 | 108 | 116 | 4 |
| 4110 | 110 | 118 | 4 |
| 4112 | 112 | 120 | 4 |

專業製造：橡膠 O 環、C 夾、迫緊、膜片、鐵氟龍、橡膠訂作規格外陸續開模中，請歡迎來電洽詢。

O 環線徑 5mm 規格

Metric-Type O-Ring Size List



單位 unit : mm

| 材質 | 橡膠 | 橡膠 (高壓) | 氟橡膠 (耐熱) | 矽橡膠 |
|----|-------|---------|----------|-----|
| | NBR70 | NBR90 | VT | SE |

| O 環 線徑 5mm 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|------------------|------------|------------|---------|
| 5005 | 5 | 15 | 5 |
| 5006 | 6 | 16 | 5 |
| 5008 | 8 | 18 | 5 |
| 5010 | 10 | 20 | 5 |
| 5015 | 15 | 25 | 5 |
| 5016 | 16 | 26 | 5 |
| 5018 | 18 | 28 | 5 |
| 5020 | 20 | 30 | 5 |
| 5025 | 25 | 35 | 5 |
| 5028 | 28 | 38 | 5 |
| 5030 | 30 | 40 | 5 |
| 5032 | 32 | 42 | 5 |
| 5034 | 34 | 44 | 5 |
| 5035 | 35 | 45 | 5 |
| 5038 | 38 | 48 | 5 |
| 5040 | 40 | 50 | 5 |
| 5042 | 42 | 52 | 5 |
| 5045 | 45 | 55 | 5 |
| 5046 | 46 | 56 | 5 |
| 5048 | 48 | 58 | 5 |
| 5050 | 50 | 60 | 5 |
| 5052 | 52 | 62 | 5 |
| 5055 | 55 | 65 | 5 |
| 5060 | 60 | 70 | 5 |
| 5065 | 65 | 75 | 5 |
| 5070 | 70 | 80 | 5 |
| 5075 | 75 | 85 | 5 |
| 5080 | 80 | 90 | 5 |
| 5085 | 85 | 95 | 5 |
| 5090 | 90 | 100 | 5 |
| 5095 | 95 | 105 | 5 |
| 5100 | 100 | 110 | 5 |
| 5102 | 102 | 112 | 5 |
| 5105 | 105 | 115 | 5 |
| 5110 | 110 | 120 | 5 |
| 5115 | 115 | 125 | 5 |
| 5120 | 120 | 130 | 5 |

| O 環 線徑 5mm 規格 | 內徑 I.D. | 外徑 O.D. | 厚度 w |
|------------------|------------|------------|---------|
| 5125 | 125 | 135 | 5 |
| 5130 | 130 | 140 | 5 |
| 5135 | 135 | 145 | 5 |
| 5140 | 140 | 150 | 5 |
| 5145 | 145 | 155 | 5 |
| 5150 | 150 | 160 | 5 |
| 5155 | 155 | 165 | 5 |
| 5160 | 160 | 170 | 5 |
| 5165 | 165 | 175 | 5 |
| 5170 | 170 | 180 | 5 |
| 5175 | 175 | 185 | 5 |
| 5180 | 180 | 190 | 5 |
| 5185 | 185 | 195 | 5 |
| 5190 | 190 | 200 | 5 |
| 5195 | 195 | 205 | 5 |
| 5200 | 200 | 210 | 5 |
| 5205 | 205 | 215 | 5 |
| 5210 | 210 | 220 | 5 |
| 5215 | 215 | 225 | 5 |
| 5220 | 220 | 230 | 5 |
| 5225 | 225 | 235 | 5 |
| 5230 | 230 | 240 | 5 |
| 5240 | 240 | 250 | 5 |
| 5245 | 245 | 255 | 5 |
| 5250 | 250 | 260 | 5 |
| 5255 | 255 | 265 | 5 |
| 5260 | 260 | 270 | 5 |
| 5265 | 265 | 275 | 5 |
| 5270 | 270 | 280 | 5 |
| 5280 | 280 | 290 | 5 |
| 5285 | 285 | 295 | 5 |
| 5290 | 290 | 300 | 5 |
| 5295 | 295 | 305 | 5 |
| 5300 | 300 | 310 | 5 |
| 5320 | 320 | 330 | 5 |
| 5325 | 325 | 335 | 5 |

專業製造：橡膠 O 環、C 夾、迫緊、膜片、鐵氟龍、橡膠訂作規格外陸續開模中，請歡迎來電洽詢。

此規格材質 NBR90、VT、SE 若有需要需詢問。

